



see what Delta can do™

VERO™ BATH COLLECTION

Its sleek vessel lavatory and minimalist showerhead are just two reasons the ribbon-inspired Vero is the perfect urban oasis.



SINGLE-HOLE
553LF
Optional escutcheon available



SINGLE-HOLE WITH RISER
753LF



8" WIDESPREAD
3553LF



3-HOLE ROMAN TUB
T2753 R2707



4-HOLE ROMAN TUB
T4753 R4707



- 18" TOWEL BAR-77718
- 24" TOWEL BAR-77724
- DOUBLE ROBE HOOK-77736
- TOWEL RING-77746
- TISSUE HOLDER-77750
- VANITY TRAY-77612



Chrome



Brilliance®
Stainless
SS

All products shown in Chrome.



MONITOR® 14 SERIES
SHOWER WITH WATER-EFFICIENT
SHOWERHEAD FEATURING
H₂OKINETIC TECHNOLOGY®
T14253-H2O R10000-UNBX

TUB & SHOWER
T14453-H2O R10000-UNBX



MONITOR® 14 SERIES
SHOWER
T14253 R10000-UNBX

TUB & SHOWER
T14453 R10000-UNBX



MONITOR 17 SERIES
TUB & SHOWER
T17453 R10000-UNBX

SHOWER ONLY
T17253 R10000-UNBX



MONITOR 17 SERIES
SHOWER WITH WATER-EFFICIENT
SHOWERHEAD FEATURING
H₂OKINETIC TECHNOLOGY
T17253-H2O R10000-UNBX

TUB & SHOWER
T17453-H2O R10000-UNBX




TEMPASSURE® 17T SERIES
SHOWER
T17253 R10000-UNBX

TUB & SHOWER
T17453 R10000-UNBX



6-SETTING DIVERTER TRIM
T11953
*Order T11853 for 3-setting
diverter trim*



BIDET
LEVER HANDLES
44-LHP H253

HANDLE BASE
RP62961



WALL MOUNT HANDSHOWER
55530
Single Setting



HANDSHOWER WITH SLIDE BAR
57530
Single Setting



All products shown in Chrome.



deltafaucet.com
800.345.DELTA (3358)
©2010 Masco Corporation of Indiana
06/10



= Water-Efficient Product

Lavatory Faucets: flow rate of 1.5 gpm versus
Industry Standard ASME A112.18.1/CSA
B125.1 of 2.2 gpm
Showerheads and Handshowers: flow rate of
1.5 gpm or 2.0 gpm versus Industry Standard
ASME A112.18.1/CSA B125.1 of 2.5 gpm



= CAVT Compliant Models Available